




EMERGENCIA 



 EMERGENCIA

PANTALLA
NBAE

CON LA FUERZA DEL LITIO.

Combine una luminaria de alta tecnología LED con un sistema de iluminación auxiliar en el caso de corte de suministro eléctrico. Combine el bajo consumo del LED con la alta eficiencia de las baterías de litio. Los avances de la técnica permiten más de 1,5 horas de autonomía con la batería interna del equipo. Esté preparado ante cualquier eventualidad.

WITH THE FORCE OF LITHIUM.

Combine a high-tech LED fixture with an auxiliary lighting system in case of power failure. Combine LED low consumption with high efficiency lithium batteries. Advances in technology allow more than 1,5 hours autonomy with the internal equipment battery. Be ready to any eventuality.

Modelo Model	LPL0620NBAE	LPL1240NBAE	LPL1550NBAE
Tensión entrada nominal Input voltage	230V	230V	230V
Frecuencia entrada nominal Input frequency	50Hz	50Hz	50Hz
Rango de frecuencia de entrada Input voltage range	50Hz-60Hz	50Hz-60Hz	50Hz-60Hz
Potencia Power	20W	40W	50W
Número de LEDs Number of LEDs	120 LEDs SMD	240 LEDs SMD	312 LEDs SMD
Flujo lumínico Lumen	2715Lm	5430Lm	6787Lm
Flujo lumínico/emergencia Lumen/emergency	750Lm	750Lm	750Lm
Batería Battery	7,4V/2200mAh	7,4V/2200mAh	7,4V/2200mAh
Duración de la batería Battery life	1,5h	1,5h	1,5h
Temperatura de color Color temperature	6000K□	6000K□	6000K□
Ángulo Angle	120°	120°	120°
Largo Length	600mm	1200mm	1500mm
Ancho x alto Width x height	80x65mm	80x65mm	80x65mm
Base y difusor Base and diffuser	Policarbonato / PC		
IP	65	65	65
IK	IK10	IK10	IK10



LPL0620NBAE
LPL1240NBAE
LPL1550NBAE



Vídeos demostrativos:
www.pritec.com/videos

