




Modelo Model	LSL03303	LSL0330	LSL06303	LSL0630
Tensión entrada Input voltage	230V	230V	230V	230V
Frecuencia Frequency	50Hz	50Hz	50Hz	50Hz
Flujo lumínico Lumen	650Lm	650Lm	1100Lm	1200Lm
Potencia Power	6W	6W	13W	13W
Temperatura de color Color temperature	3000K <input type="checkbox"/>	4000K <input type="checkbox"/>	3000K <input type="checkbox"/>	4000K <input type="checkbox"/>
Dimensiones Size	300x50x50mm		600x50x50mm	
Material base Base material	Aluminio / Aluminum			
Material difusor Diffuser material	Plástico translúcido / Translucent plastic			
Material tapa Cover material	Plástico plata / Silver plastic			
Ángulo Angle	120°	120°	120°	120°
IP	40	40	40	40



Es posible solicitar todas las versiones de LSL con un interruptor lateral para su encendido. (Coste adicional).



LSL0330
LSL03303



LSL0630
LSL06303

Es posible solicitar la rotulación del aplique con la información solicitada.

TERCERO

SEGUNDO

PRIMERO

APLIQUE LED AVANZADO

SEGURIDAD Y ESTILO.

El aplique avanzado pensado para rellanos, ascensores y escaleras entre otras aplicaciones, combina la seguridad con el estilo. Aporta grandes ventajas dado el uso habitual de esta gama de productos. Inmune a continuos encendidos y apagados, bajo consumo.

SAFETY AND STYLE.

The advanced wall light designed for landings, elevators and stairs among other applications, combines safety with style. It brings great advantages given the habitual use of this range of products. Immune to continuous on and off, low consumption.

