



Modelo Model	P6P40X4B2N	P6P40X6B2N	P6P40X4B2R	P6P40X6B2R	P6P40X4B2RDL	P6P40X6B2RDL	P6P40X4B2RTR	P6P40X6B2RTR
Tipo de instalación Installation type	Desmontable Removable		Desmontable Removable		Desmontable Removable		Desmontable Removable	
Potencia Power	40W		40W		40W		40W	
Tensión de entrada Input voltage	230V		230V		230V		230V	
Frecuencia Frequency	50Hz		50Hz		50Hz		50Hz	
Factor de potencia Power factor	>0.97		>0.97		>0.97		>0.97	
Temperatura de color Color temperature	4000K □	6000K □	4000K □	6000K □	4000K □	6000K □	4000K □	6000K □
CRI	>0.82		>0.82		>0.82		>0.82	
Luminosidad nominal Lumen	5310Lm	5380Lm	5310Lm	5380Lm	5310Lm	5380Lm	5310Lm	5380Lm
Dimensiones Size	595x595x30mm		595x595x30mm		595x595x30mm		595x595x30mm	
Regulable	No		Bus 1-10v		DALI		Corte de Fase	
IP	40		40		40		40	
Ángulo Angle	150°		150°		150°		150°	



Todos nuestros productos con salida a cable, incluyen conexiones rápidas **WAGO** para facilitar, mejorar y agilizar la instalación.



La tecnología de retroiluminación permite una mejor uniformidad del flujo luminoso así como un mayor rendimiento que los paneles convencionales LED. La luz sale directa de la luminaria sin necesidad de ser refractada.



P6P40X4B2N
P6P40X6B2N
P6P40X4B2R
P6P40X6B2R
P6P40X4B2RDL
P6P40X6B2RDL
P6P40X4B2RTR
P6P40X6B2RTR

GRANDES VENTAJAS.

La gama B2N ofrece grandes diferencias frente a sus competidores. Un panel retroiluminado, con una mejor distribución lumínica y menor deslumbramiento que los paneles finos. Ligero pero robusto, lo que permite una instalación fácil ayudado de las fichas de conexión sin herramientas. Alto factor de potencia y driver aislado de gran calidad.

GREAT ADVANTAGES.

The B2N range offers great differences compared to its competitors. A backlit panel, with better light distribution and less glare than thin panels. Lightweight but robust, allowing easy installation with the help of the connection tabs without tools. High power factor and high quality isolated driver.

PANEL
LED B2
600x600

